FUNCTIONAL FEATURES

DESIGN **FEATURES**



LED Flashers





Dual Channel ABS



Super Wide 140 mm . Radial Rear Tyre



Upside Down Front Forks





Grey Colour Muffler Guard*



Grey Colour Aluminium Swingarm*

*Available only on R15M

Authorised Dealer

COLOUR VARIANTS









Constant mesh, 6-speed

Electric starter

type	Deltabox
suspension system	Telescopic Upside Down Fork (USD Fork
uspension system	Linked-Type monocross suspension
type (front)	Disc brake (282 mm)
type (rear)	Disc brake (220 mm)
ze (front)	100/80-17M/C 52P - Tubeless
ze (rear)	140/70R17M/C 66H - Radial tubeless
ube diameter of front fork	37.0 mm
	Dual channel

E20 compatible Starting system type

Transmission type

Other Information

Shift timing li VVA indicator Quick shifter i Fuel consumption

SPECIFICATIONS

Engine type Liquid cooled, 4-stroke, SOHC, 4-valve 155 cc Displacement 58.0 x 58.7 mm Bore x stroke Compression ratio 13.5 kW(18.4PS)/10000 r/min Maximum horse power Maximum torque 14.2 N·m(1.4kgf·m)/7500 r/min Fuel injection Fuel system Wet, multiple-disc Clutch type

erall length	1990 mm
erall width	725 mm
erall height	1135 mm
t height	815 mm
eelbase	1325 mm
imum ground clearance	170 mm
b weight th oil and a full fuel tank)	141 kg
I tank capacity	11 <i>l</i>

	12 V, 4 Ah Bi-functional LED (Class D)	Clock	Digital, auto adjust with smartphone connectivity
	LED	Riding Modes	Track mode / Street mode
t	LED	Dual horn	Equipped
	Digital Digital	Y-Connect (Smartphone Bluetooth Connectivity)	Equipped
	Digital	Side stand engine cut-off switch	Equipped
ght	Equipped	Traction control system	Equipped
	Equipped	Quick shifter (up-shift)	Equipped
indicator	Equipped	Colour TFT Meter	Equipped
otion indicator	Equipped		

The specifications and designs of the motorcycles shown here may vary according to the requirements and are subject to change without prior notice. Colorus shown may not match the actual colour due to printing limitations. Conditions apply. **Warranty extended for engine, FI system, AIS system and Electricals including wiring harness, whichever is earlier. 5-Year warranty* only applicable in case of purchase of Yamaha Protection Plus Policy during validity period. Please refer to Yamaha Protection Plus Policy for more details.

Yamaha Motor India Sales Pvt. Ltd., AKDR Tower-5th Floor, Door No. 3/381, Rajiv Gandhi Salai (OMR) Mettukuppam, Chennai - 600097. Phone: 044-3814 7000. Toll Free No.: 1800 420 1600 Email: info@yamaha-motor-india.com www.yamaha-motor-india.com





FI ENGINE

155cc LC4V SOHC

The liquid cooled single overhead camshaft fuel injected engine churns out a maximum horse power of 19.5kW(18.4PS)/10000r/min and maximum torque of 14.2N • m(1.4kgf • m)/7500r/min.



TRACTION CONTROL SYSTEM





ASSIST & SLIPPER CLUTCH









SMS & EMAIL

CALL ALERT

PHONE BATTERY
LEVEL STATUS

App APP CONNECTIVITY STATUS





Now the R15M has a full colour TFT meter inspired by the R1 . Stay informed of all that happens with the advanced instrument cluster screen.

> WITH TRACK MODE & STREET MODE



QUICK SHIFTER INDICATOR

STREET MODE

Coolant Temperature

Average Mileage

Average Speed

Battery Power

TRACTION CONTROL SYSTEM INDICATOR

ommon to both Track & Street Mode)

TRACK MODE

Latest Lap Time

Fastest Lap Time



Stay connected even on the move. Y-Connect is Yamaha's latest innovation that lets you link your smartphone directly to your Yamaha motorcycle.